



Part No.	Dimensions (inch)									
	A	B	C	D	E	L	P	S	T	N
	±0.15	+0.05 -0.00	+0.62 -0.31	±0.10	Angle	±0.15	+0.10 -0.40	±0.05	±0.05	Thread UNF-3A
GC 4-5	2.250	0.250	1.250	0.875	40	1.290	0.550	0.188	0.625	5/16-24
GC 5-5	2.250	0.313	1.250	0.875	40	1.290	0.550	0.188	0.625	5/16-24
GC 5-6	2.250	0.313	1.250	0.875	36	1.290	0.550	0.188	0.625	3/8-24
GC 5-8	2.500	0.313	1.500	1.000	38	1.540	0.550	0.250	0.750	1/2-20
GC 6-8	2.500	0.375	1.500	1.000	38	1.540	0.550	0.250	0.750	1/2-20
GC 6-10	3.375	0.375	2.000	1.125	24	2.040	0.550	0.375	0.825	5/8-18
GC 6-12	3.375	0.375	2.000	1.125	18	2.040	0.800	0.375	0.825	3/4-16
GC 7-8	3.375	0.438	2.000	1.125	30	2.040	0.550	0.375	0.825	1/2-20
GC 7-10	3.375	0.438	2.000	1.125	24	2.040	0.700	0.375	0.825	5/8-18
GC 8-10	3.375	0.500	2.000	1.125	24	2.040	0.700	0.375	0.825	5/8-18
GC 8-12	3.375	0.500	2.000	1.125	18	2.040	0.800	0.250	0.825	3/4-16
GC 8-12-1	3.375	0.500	2.000	1.125	18	2.040	0.700	0.375	0.825	3/4-16

Code of thread: left-handed thread - L , E.g. GC 5- 5 L.

Material and surface treatments:

1) Medium carbon steel. Coated with rust-proof oil or zinc plating.

2) Alternative stainless steel 304 or stainless steel 316.

Specials on request (only volumes).